XN10 CRAWLER EXCAVATOR

National toll-fre

This product has a high configuration superior performance low fuel consumption, wide operating range. It is suitable for loosing soil of greenhouses, parks and forest departments of municipalities, tree planting, nurseries, concrete breaking, sand-gravel material mixing, construction work in tight spaces etc. A quick hitch can added for easy changing of attachments, like auger, hydraulic hammer, bulk bucket, grab, etc. It can reduce maintenance and operating costs. Low investment means high returns. Less labor involved.

DIMENSIONS	UNIT	VALUE
Wheel base	mm	770
Track length	mm	1090
Upper chassis ground clearance	mm	380
Counter weight turning radius	mm	733
Chassis width	mm	946
Track width	mm	180
Track length	mm	320
Transportation length	mm	1330
Total height	mm	2550
Max. digging radius on ground	mm	2400
Max. d.iggin depth	mm	1400
Max. digging height	mm	2490
Max. dumping height	mm	1750
Max, digging depth	mm	1320
Min. turning radius	mm	1190
Blade lift	mm	325
Blade dozing depth	mm	175
Machine weight	kg	870
Bucket capacity	m3	0.02
Rated power	kW	8.6



The technical information, pictures may be a little different to the real product, any amendments changes without notice, we reserve the right of final interpretation.



